


Electric Powered Lift Platforms ถาดยกพาเลท แบบไฟฟ้า







Increase efficiency & reduce production time.

- For assembly lines & loading / unloading operations with / without pallets.
- 'Superlow', 'U' shape model allows pallet truck access in lowered position and stacker access at any level.
- No pit required and 'plug and play' feature ensures instant usage.
- Remote power and control unit provides ease of operation and maintenance.

Model รุ่น		ELP1.0-U	ELP1.5-U
Capacity น้ำหนักบรรทุก	kg	1000	1500
Min. Platform Height (H) ความสูง ขั้นต่ำถาดยก	mm	82	105
Max. Platform Height (H1) ความสูง สูงสุดถาดยก	mm	760	860
Platform Size (L x B) ขนาดถาดยก	mm	1450 x 1140	1600 x 1180
Width between Fork (B2) ความกว้างระหว่างงายก	mm	585	585
Lifting Time เวลาในการยก	sec	18	30
Lifting Speed with Load ความเร็วในการยกขณะบรรทุก	mm/s	42	30
Lowering Speed with Load ความเร็วในการลงขณะบรรทุก	mm/s	48	40
Motor มอเตอร์	kw	0.75	1.5
Net Weight น้ำหนักสุทธิ	kg	250	380




The tried and trusted lift table with study construction.

Single Scissor Electric Lift Platforms with Pendant Stand

ถาดยกพาเลท แบบไฟฟ้า แยกชุดปั้ม Compact hydraulic design with all safety components complying to En 1570, High pressure cylinder with dual safety function.


•		
Model รุ่น		ELP1.0-SC
Capacity น้ำหนักบรรทุก	kg	1000
Min. Platform Height ความสูง ขั้นต่ำถาดยก	mm	82
Max. Platform Height ความสูง สูงสุดถาดยก	mm	760
Platform Size (W x L) ขนาดถาดยก	mm	1450 x 1140
Lift Speed ความเร็วในการยก	sec	18
Lifting Time เวลาในการยก	mm/s	42
Lowering Speed ความเร็วในการลง	mm/s	48
Motor มอเตอร์	kw	0.75
Net Weight น้ำหนักสทธิ	ka	250

- With emergency switch off and a 3m long control cable.
- Hard chrome plated piston rods.
- Lift and lower by easily push buttons to reach the ergonomically correct working height.



Extra Long Electric Lift Platforms

ถาดยกพาเลท แบบไฟฟ้า ถาดยาวพิเศษ



- · Heavy duty design.
- Meet EN1570 norm and ANSI/ASME safety standards.
- · These models can be used in above-floor or in-floor pit applications.

Standard Safety Features

- Upper platform lifted with aluminum safety bar preventing descent on contact with obstructions.
- · Low-tension (24V) control box with up-down buttons and compensated flow valve for controlled lowering speed.
- · Heavy duty cylinders with drainage system and check valve to stop the lift table lowering in case of hose burst.
- · Safety clearance between scissors to prevent trapping during operation.

Other Standard Features

- · Self lubricating bushings on pivot points.
- · Removable lifting eye to facilitable handling and lift table
- · High quality AC power packs are made in Europe.



Model รุ่น		ELP2.0-EL	ELP4.0-EL	ELP8.0-EL
Capacity น้ำหนักบรรทุก	kg	2000	4000	8000
Min. Platform Height ความสูง ขั้นต่ำถาดยก	mm	205	230	240
Max. Platform Height ความสูง สูงสุดถาดยก	mm	1000	1000	1000
Platform Size (W x L) ขนาดถาดยก	mm	2000 x 820	2500 x 850	3000 x 1200
Base Frame Size ขนาดโครงสร้าง(ฐาน)	mm	2460 x 640	2450 x 785	2970 x 930
Lift Speed ความเร็วในการยก	sec	40-45	30-40	35-45
Motor มอเตอร์	kw	1.1	2.2	2.2
Net Weight น้ำหนักสุทธิ	kg	265	360	705