

ELP-EU Single Scissor Electric Lift Platforms

ถาดยกพาเลท แบบไฟฟ้า

Multiple uses such as: lifting and lowering materials, - level compensation when fitting machines, installation in conveyor system, etc.

- No pit required when purchased with optional steel ramp for pallet truck access.
- Built in hydraulic power pack with remote control panel.
- 'Plug and play' feature ensures instant usage.
- Compact hydraulic design with all safety components complying to EN1570.
- High pressure cylinder with dual safety function.
- Hard chrome plated piston rods.
- Lift and lower by operating pendant to reach the ergonomically correct working height.
- With emergency switch off and a 3m long control cable.
- With different loading capacity up to 4000kg for your option.



Model รุ่น		ELP1.0-EU	ELP2.0-EU	ELP3.0-EU	ELP4.0-EU
Capacity น้ำหนักบรรทุก	kg	1000	2000	3000	4000
Min. Platform Height สามารถยกขั้นต่ำ	mm	190	190	220	300
Max. Platform Height ความสามารถสูงสุด	mm	1010	1010	1020	1400
Platform Size (W x L) ขนาดถาดยก	mm	1300 x 800	1300 x 800	1300 x 800	1200 x 2200
Lift Speed ความเร็วในการยก	sec	25	40	26	45-50
Lifting Time เวลาในการยก	mm/s	40	22	30	31
Lowering Speed ความเร็วในการลง	mm/s	35	33	40	35
Motor มอเตอร์	kw	0.75	0.75	1.5	2.2
Net Weight น้ำหนักสุทธิ	kg	220	280	320	505

DSELP

Double Scissor Electric Lift Platforms,
ถาดยกพาเลท แบบไฟฟ้า



- Heavy Duty Design.

TSELP

Triple Scissor Electric Lift Platforms,
ถาดยกพาเลท แบบไฟฟ้า



- Heavy duty design.

QSELP

Quadruple Electric Lift Platforms,
ถาดยกพาเลท แบบไฟฟ้า



- Small capacity for four scissor lift table.

Model รุ่น		DSELP1.0	DSELP2.0	DSELP4.0	TSELP1.0	TSELP2.0	QSELP0.4	QSELP0.8
Capacity น้ำหนักบรรทุก	kg	1000	2000	4000	1000	2000	400	800
Min. Platform Height ความสูงขั้นต่ำถาดยก	mm	305	360	400	470	560	600	706
Max. Platform Height ความสูงสูงสุดถาดยก	mm	1780	1780	2050	3000	3000	4140	4210
Platform Size (W x L) ขนาดถาดยก	mm	1300 x 820	1300 x 850	1700 x 1200	1700 x 1000	1700 x 1000	1700 x 1000	1700 x 1000
Base Frame Size ขนาดโครงสร้าง(ฐาน)	mm	640 x 1240	785 x 1220	900 x 1600	1600 x 1000	1606 x 1010	1000 x 1600	1010 x 1606
Lift Speed ความเร็วในการยก	sec	35-45	35-45	55-65	35-45	50-60	30-40	70-80
Motor มอเตอร์	kw	2.2	2.2	2.2	2.2	2.2	2.2	2.2
Net Weight น้ำหนักสุทธิ	kg	210	295	520	450	750	548	858

Standard Safety Features

- Upper platform lifted with aluminum safety bar preventing descent on contact with obstructions.
- Internal power pack equipped with relief valve against overloading and compensated flow valve for controlled lowering speed.
- Cylinders with drainage system and check valve to stop the lift table lowering in case of hose burst.
- Safety clearance between scissors to prevent trapping during operation.
- Meets EN1570 norm and ANSI/ASME safety standard. • High quality power unit made in Europe.

Other Standard Features

- These models can be used in above-floor or in-floor pit applications.
- Self lubricating bushings on pivot points. • Removable lifting eye to facilitate handling and lift table installation.